

The UniGrip – Y-Fit is a cable suspension product designed for the fast suspension of electrical conduit and tray, or lighting.


FEATURES / BENEFITS

- Quick up to 6 times faster than traditional suspension systems
- **Easy** integral ergonomically designed release button allows for simple adjustment
- Secure button acts as a locking screw and indicator clearly highlights the wire is locked in position for ultimate security. Side cable exit keeps cable away from working area
- Versatile designed for lighting or containment, dual fixing points for balance. 6" / 150 mm, 12" / 300 mm and 18" / 460 mm leg lengths as standard with a variety of cable end fixings eg. Toggle, Hook etc. Grub screw can be adjusted with a 5/32" hex key in order to adjust the legs
- Strong highest load rating 240 lbs / 110 kg with 5:1 SWL




INSTALLATION & ADJUSTMENT










Maximum off axis suspension = 15° (Unless otherwise specified by Gripple Technical Services),

The safe working load is calculated based on the cable exiting on axis. For off-axis please contact Gripple Canada Technical Services.

SPECIFICATION



No. 2	Dimension	А	В	С
	Inches	3 1/8	11/16	13/16
	mm	80	17	20

No. 3	Dimension	А	В	С
	Inches	3 3/4	11/16	7/8
	mm	96	17	22

Y-Fit Adapter - Mild Steel (Type EN1A) - Bright Foot Grub Screw - Mild Steel (Type EN1A) - Bright Zinc Plated

AVAILABLE END FIXINGS



For more options on available end fixings please contact us or visit www.gripple.com

SUBMITTAL INFORMATION

Load Rating:

No. 2 - 120 lbs / 55 kg at 5:1 safety factor No. 3 - 240 lbs / 110 kg at 5:1 safety factor

Material:

Housing - Type ZA2 Zinc

Carriage - Acetal Copolymer
Wedge - Sintered steel hardened to min. 56

Rockwell C

Button - Acetal Copolymer

Approvals: CSA & UL 1598 & UL 2239 NOT suitable for use in chlorinated / swimming pool

BUS-PI-UNI-CAN-ENG-3289 Published July 2021





















