Mini Helix Screw



Accessory

A secure, low profile screw designed for the fast installation and easy adjustment of polyester fibre acoustic panels.

FEATURES / BENEFITS

- Strong the helical screw binds layers of polyester fibre to form a strong anchoring point
- Easy - the hanger can tilt to one side, acting as a lever for even easier insertion
- Quick with the hanger and anchor pre-assembled, installation time is . reduced
- Adjustable easy height adjustment when using Mini Helix Screw with Express, Standard Hanger or InvisiGrip





INSTALLATION 1. 2. З. 4 (U) (C)

RELATED PRODUCTS SPECIFICATION Size Dimension For more options on related products please contact us or visit www.gripple.com 3/8" 10 mm А В 1 7/16" 36.6 mm SUBMITTAL INFORMATION С 7/8" 23 mm Load Rating: Max. load rating of this product in a vertical suspension = 33 lb /15 kg. Max. load ratings will vary due to the type of acoustic panel material being used. Gripple cannot guarantee a SWL due to this factor. If unsure please contact Gripple Technical Services. To test suitability with a specific material Gripple will take a sample of material and perform a pull out test to accurately advise the customer. Minimum recommended panel thickness in vertical = 12 mm Material: Foot - Nylon (Glass fill 30%) $\bigotimes \bigotimes \bigotimes$

BUS-PI-ACC-CAN-ENG-3204 Published September 2020

www.gripple.com

Gripple's policy is one of continuous development and innovation. We therefore reserve the right to alter specifications, etc. without notice. Gripple Canada | 6665 Tomken Road | Units 9 -10 | Mississauga | ON | L5T 2C4 Tel +1 905-458-8700 Email cainfo@gripple.com

 (\mathcal{X})