

End Fixing

For quick and secure connection to the Gripple Catenary system.

FEATURES / BENEFITS

- Allows horizontal and vertical adjustment via a Gripple hanger
- Cams lock in place even at angles up to 60° from horizontal
- Can be fitted retrospectively
- Available in two versions to suit 1/8" and 1/4" Catenary
- Supplied as ready-to-use kit with Gripple fastener and length of cable
- Available in lengths of 5 ft 30 ft as standard
- Independently certified



INSTALLATION


1.







SPECIFICATION



| Size | А | | В | | С | |
|------|-------|----|-------|----|--------|----|
| | in | mm | in | mm | in | mm |
| 1/8" | 1/2 | 13 | 1 | 25 | 1 5/16 | 33 |
| 1/4" | 15/16 | 24 | 1 3/4 | 44 | 1 3/4 | 44 |

SUBMITTAL INFORMATION

Safe Working Load:

Refer to Gripple Technical Services for catenary span loads.

Material:

Housing - Type ZA2 Zinc

Locking cams - Sintered steel hardened

to min. 56 Rockwell C Spring - Stainless Steel (Type 302)

Approvals:

Lloyds certified **UL** Listed

AVAII ABI F FASTENERS



For more options on available fasteners please contact us or visit www.gripple.com

IMPORTANT RECOMMENDATIONS

- 1. Construction materials and conditions vary on different sites. If it is suspected that the base material has insufficient strength to achieve a suitable fixing, contact Gripple Canada Inc. The responsibility for judgement of base material strength lies with the installer, and not with Gripple Canada Inc.
- 2. Not to be used in marine, coastal or corrosive environments
- 3. The information and recommendations given herein are believed to be correct at time of writing. The data has been obtained from tests done under laboratory, or other controlled conditions and it is the user's responsibility to use the data given in light of conditions on site, taking account of the intended use of the products concerned
- 4. Whilst Gripple Canada Inc. can give general guidance and advice, the nature of Gripple products means that the ultimate responsibility for selecting the correct product for a particular application must lie with the customer.
- 5. All products must be used, handled and applied in accordance with current product instructions and manufacturers recommendations for use, published by Gripple Canada Inc.

























