




















Accessories & Tools











A range of tools and accessories to complement the Gripple hanging kits and to make their installation quick and easy




- Anchoring Solutions
- Beams & Purlins
- Brackets & Attachments
- Adaptors
- UniGrip & Hanger Accessories
- Tools & Finishing Accessories















Product information	Size	Product code	Order Quantity
DROP IN ANCHOR			
	<ul style="list-style-type: none"> • ETA approved, suitable for use in non-cracked concrete • 3:1 safety factor (M6 SWL 90 kg, M8 SWL 90 kg, M10 SWL 225kg) 		
	M6	DPA-M6	10
	M8	DPA-M8	10
	M10	DPA-M10	10
SETTING PUNCH (FOR DROP-IN ANCHOR)			
	<ul style="list-style-type: none"> • For use with a hammer, leaves 4 identifiable marks to indicate correct anchor installation 		
	M6	MAN-PUNCH-M6*	1
	M8	MAN-PUNCH-M8*	1
	M10	MAN-PUNCH-M10*	1
SETTING TOOL (FOR DROP-IN ANCHOR)			
	<ul style="list-style-type: none"> • Mechanical setting tool available in M6, M8 and M10, for use with a standard drill 		
	M6	MECH-PUNCH-M6*	1
	M8	MECH-PUNCH-M8*	1
	M10	MECH-PUNCH-M10*	1
CONCRETE WIRE ANCHOR			
	<ul style="list-style-type: none"> • CSTB test report • Made from high tensile stainless steel • SWL 45 kg, 3:1 safety factor 		
	M8	WIRE-ANCHOR	1
SETTING TOOL (FOR WIRE ANCHOR)			
	<ul style="list-style-type: none"> • Aids positioning and installation of wire anchor • Improves surface area and surface to hammer 		
	M8	WIRE-ANCHOR-TOOL	1
CRACKED CONCRETE RING ANCHOR			
	<ul style="list-style-type: none"> • Suitable for cracked concrete • ETA approved, F90 fire resistance • SWL 53 kg, 3:1 safety factor 		
	M6	CCRA6	1
CONCRETE CEILING ANCHOR			
	<ul style="list-style-type: none"> • Expands when under load • SWL 45 kg, 3:1 safety factor 		
	M6	CWH6	1
CONCRETE SCREW (Suitable for cracked and non-cracked concrete)			
	<ul style="list-style-type: none"> • Anchor is driven directly in to base material • Max load of 100 kg in C20/25 concrete • Drill a 6 mm pilot hole • A/F 13 mm spanner or Torx® #30 driver bit 		
	6.0 x 40 mm	CS40	1










Product information	Size	Product code	Order amount
TOOL FOR CONCRETE SCREW			
	<ul style="list-style-type: none"> Use with the concrete screw - type :Torx® #30 driver bit 	CONC-SCREW-BIT	1
BARREL CONCRETE SCREW			
	<ul style="list-style-type: none"> Quick and easy operation Max load of 100 kg in C20/25 concrete Drill a 6 mm pilot hole 	M8 BCS35-M8	1
STUD CRACKED CONCRETE SCREW (Suitable for cracked and non-cracked concrete)			
	<ul style="list-style-type: none"> One size fits both M8 and M10 Max load of 100 kg C20 and C25 concrete Drill a 6 mm pilot hole A/F 13 mm spanner 	8.0 x 60 mm SCCS35	1
CEILING CLIP CONCRETE SCREW			
	<ul style="list-style-type: none"> For screwing into concrete Loop end engages into the valley of the clip, allowing pivotal movement once installed 	6.0 x 40 mm CLIP-CCS40	10
CEILING CLIP WOOD SCREW			
	<ul style="list-style-type: none"> Loop end engages into the valley of the clip, allowing pivotal movement once installed Weight loadings are dependent on the wood being screwed into and are not guaranteed 	32 mm CLIP-W32	10
CONCRETE WOOD SCREW (CWS32)			
	<ul style="list-style-type: none"> Easy-fit slotted/hex head screw suitable for wood and non-cracked concrete installation Ideal for use with the Eyelet and 90° Eyelet end fixings 3:1 safety rating - load rating is dependant on base material 	6.0 x 32 mm CWS32	1
CONCRETE WOOD SCREW (CWS-5X32)			
	<ul style="list-style-type: none"> Easy-... Ideal for use with the Top Hat end fixing 3:1 safety rating - load rating is dependant on base material 	5.0 x 32 mm CWS-5X32	1
INSTALLATION TOOL (FOR CEILING CLIP FOR WOOD)			
	<ul style="list-style-type: none"> For use with a hammer-action drill Easily secures the ceiling clip into wood 	HF-SOCKET-8MM	1
BARREL WOOD SCREW			
	<ul style="list-style-type: none"> For anchoring into wood Ideal for use with No.1 M6 and M8 barrel hanger kits SWL 10 kg, weight loadings are dependent on the wood being screwed into and are not guaranteed 	M6 x 50 mm M8 x 50 mm BWS35-M6 BWS35-M8	1 1
SPRING CLIP			
	<ul style="list-style-type: none"> Spring action prevents pull-out SWL 30 kg, 3:1 safety factor For use on busbar, high-bay and strip lighting 	6 mm - 8 mm CLIP-SPG-68	1
M6 & M8 ADAPTOR			
	<ul style="list-style-type: none"> Comes with corresponding serrated nut SWL 90 kg (M6) and 225 kg (M8), 5:1 safety factor Can be fixed into concrete using a Drop-in anchor 	M6 M8 ADP-M6 ADP-M8	1 1













Product information	Size	Product code	Order amount
WEDGE NUT			
	<ul style="list-style-type: none"> • For fastening quickly and securely into decking • SWL 90 kg (M6 x 18 mm), 180 kg (M6 x 20 mm and M6 x 25 mm) and 200 kg (M8 x 20 mm and M8 x 25 mm) • 3:1 safety factor 		
	M8 x 18 mm	WEDGE8-18	1
	M8 x 25 mm	WEDGE8-25	1
PIGTAIL			
	<ul style="list-style-type: none"> • For fast and secure fixing of Loop end. Ideal for signage and banners • SWL 90 kg (M6 x 20 mm and M8 x 25 mm) and 150 kg (M8 x 45 mm), 5:1 safety factor • Does not include drop-in anchor 		
	M6 x 20 mm	PIGTAIL6-20MM	1
	M6 x 45 mm	PIGTAIL6-45MM	1
	M8 x 45 mm	PIGTAIL8-45MM	1
T-BAR TWIST CLIP			
	<ul style="list-style-type: none"> • M6 Twist clip for supporting fittings, etc. below the ceiling grid • SWL 22 kg, 5:1 safety factor • Suitable for use with Barrel end fixing 		
	M6	TBAR-CLIP-M6	1
LSK CLIP			
	<ul style="list-style-type: none"> • General purpose clip to support light fittings • Steel with zinc plated finish • SWL 8 kg, 5:1 safety factor 		
		CLIP-LSK	1
VERTICAL FLANGE CLIP			
	<ul style="list-style-type: none"> • Available in two sizes to suit thicknesses 1 mm to 7 mm • SWL 24.5 kg, 3:1 safety factor 		
	1 mm to 5 mm	GCVF15	1
	5 mm to 7 mm	GCVF57	1
BEAM CLIP			
	<ul style="list-style-type: none"> • Available in a variety of sizes to attach to different beam thicknesses • SWL 32.3 kg, 3:1 safety factor 		
	2 mm to 4 mm	GCB24	1
	4 mm to 8 mm	GCB48	1
	8 mm to 14 mm	GCB814	1
	14 mm to 20 mm	GCB1420	1
Z PURLIN CLIP			
	<ul style="list-style-type: none"> • Suitable for purlins of thickness 2.5 mm maximum • SWL 16.3 kg, 3:1 safety factor 		
	Max 2.5 mm	GCZP48	1
PURLIN CLIP			
	<ul style="list-style-type: none"> • Suitable for purlins of thickness 4 mm to 5 mm • SWL 6.8 kg, 3:1 safety factor 		
	4 mm to 5 mm	GCP45	1
TIGER CLIP			
	<ul style="list-style-type: none"> • Hammer-on installation • SWL 40.8 kg, 3:1 safety factor 		
	Tiger Clip 28	TIGERCLIP-28	1
	Tiger Clip 816	TIGERCLIP-816	1
CATENARY STEEL ANCHOR			
	<ul style="list-style-type: none"> • Designed for blind fixing where only one side of beam is accessible • Ideal for use with Catenary Kits 		
	Catenary Steel Anchor	CAT-STEEL-ANCHOR	1

Product information	Size	Product code	Order amount
GF-BRACKET			
	<ul style="list-style-type: none"> Ideal for clamping onto an I-Beam, designed for use with M12 threaded rod (not supplied) SWL 340 kg, 5:1 safety factor 		
	I Beam 8 mm / 16 mm	GF16-EYENUT-12	1
	I Beam 10 mm / 19 mm	GF20-EYENUT-12	1
	I Beam 18 mm / 30 mm	GF30-EYENUT-12	1
EYEBOLT			
	<ul style="list-style-type: none"> Available in a wide variety of sizes, lengths and thread lengths to suit a variety of applications SWL 325 kg, 5:1 safety factor 		
	M8 x 60 mm	EYEBOLT-M8-60MM-F/TH	10
	M8 x 130 mm	EYEBOLT-M8-130MM-F/TH	10
	M8 x 98 mm	EYEBOLT-M8-200MM-98MM	10
	M8 x 200 mm	EYEBOLT-M8-0.2M-F/TH	10
	M10 x 130 mm	EYEBOLT-M10-130MM-F/TH	10
	M10 x 98 mm	EYEBOLT-M10-200MM-98MM	10
TURNBUCKLE			
	<ul style="list-style-type: none"> For cold room panels Available in 8 mm or 10 mm with thread lengths 80 mm and 200 mm SWL 325 kg, 5:1 safety factor 		
	M8 X 200 mm	TBK8-R200	10
	M10 X 200 mm	TBK10-R200	10
M8 DECKING ADAPTOR			
	<ul style="list-style-type: none"> Ideal for use with Loop, Snap hook and especially Y-Fit's SWL 90 kg, 3:1 safety factor Can be combined with other decking fixings on request 		
	8x25 mm wedge	ADP-M8-W25	10
	Alphawedge	ADP-M8-A	10
	Multiwedge	ADP-M8-M2	10
	TR 60 wedge	ADP-M8-TR60	10
	MF wedge	ADP-M8-MF	10
UNIGRIP #2			
	Standard	UG2-10BB	10
	M8 Stud Channel Nut	UG2-CN-10BB	10
	M8 Stud Flange Nut	UG2-FN-10BB	10
	Quarter Turn (QT)	UG2-QT-10BB	10
	Quarter Turn (QTUB)	UG2-QTUB-10BB	10
	Hook	UG2-HK-10BB	10
	Calibra	UG2-CAL-10BB	10
UNIGRIP #3			
	Standard	UG3-10BB	10
	M10 Stud Channel Nut	UG3-CN-10BB	10
	M10 Stud Flange Nut	UG3-FN-10BB	10
	Quarter Turn (QT)	UG3-QT-10BB	10
	Quarter Turn (QTUB)	UG3-QTUB-10BB	10
UNIGRIP #4			
	M12" Stud Channel Nut	UG4-CN-5BB	10
	M12" Stud Flange Nut	UG4-FN-5BB	10

Product information	Size	Product code	Order amount
DUCT TRAPEZE			
	<ul style="list-style-type: none"> • Suitable for rectangular ducting from 0.6 - 1.5mm gauge steel • Rubber pad included to prevent leakage • SWL 45 kg, 5:1 safety factor 		
	No.2	DT2-ACC-PAD	10
TRAPEZE PLUS ACCESSORY			
	<ul style="list-style-type: none"> • SWL 45 kg, 3:1 safety factor (only to be sold with Fire Rated Kits) 		
	No.2	MTZ2-10BB	10
	No.3	MTZ3-10BB	10
	No.4	MTZ4-10BB	10
TWIST CLIP WHITE (TCW)			
	<ul style="list-style-type: none"> • Ideal for hanging from suspended ceiling T-Bar, signage, acoustic baffles or luminaires • Designed for use with the Angel range • Quick and easy to install - no tools required 		
	40 mm x 32 mm x 15 mm	TWIST-CLIP-WHT-P142371	1
FIRE RATED CLIP			
	<ul style="list-style-type: none"> • Fire rated cable fastener for direct suspension of cables to ceilings or walls • Quick installation reduces labour costs • Holds up to 16 cables (double version) 		
	145 mm	FRC-S-100-P-SS-F	100
	260 mm	FRC-D-100-P-SS-F	100
TRAPEZE BRACKET			
	<ul style="list-style-type: none"> • Easily attached to rectangular ducting; replaces the need for threaded rod or channel support • Rigid 2 mm steel thickness with galvanised finish • Use with UniGrip No. 2 and No. 3 		
	2 mm	TPZ-BRACKET	10
BEAM CLAMP			
	<ul style="list-style-type: none"> • Avoids drilling into and welding onto I-beams • Simple and easy to install with an aesthetic appeal • Compatible with Gripple Stud End Fixing; 4:1 safety factor 		
	M8 (SWL 110 KG)	BEAMCLAMP-M8	1
	M10 (SWL 240 KG)	BEAMCLAMP-M10	1
	M8 (SWL 110 KG)	BEAMCLAMP-M8-EYE	1
QT ACCESSORY			
	<ul style="list-style-type: none"> • Simple quarter turn attachment to bracket • Enables pipes of different sizes to be installed along the centre axis • Allows condensate pipes to be installed at a gradient for drainage • Replaces more than 13 different pipe ring sizes, when used with the Gripple Universal Bracket 		
	M8	GC2-QTA-M8	100
LINK-HOOK			
	<ul style="list-style-type: none"> • Easy to attach and detach for loading cable tray • Use with the Y-Fit and Y-Fit accessory • SWL 45 kg, 4:1 safety factor 		
	6 x 48 mm	LINK-HOOK	1
FAST TRAK ADAPTER			
	<ul style="list-style-type: none"> • Metal decking adapters for Fast Trak. Available in quantities of 10 or 100 with M10 or M8 washer 		
	M10 Square Washer	FTA-M10-100P	100
	M10 Square Washer	FTA-M10-10P	10
	M8 Square Washer	FTA-M8-100P	100
	M8 Square Washer	FTA-M8-10P	10

Product information	Size	Product code	Order amount
CABLE BASKET CLIP (CB)			
 <ul style="list-style-type: none"> Prevents uplift and slide of cable basket Four sizes available to fit 4 mm and 5 mm cable basket wire Tool-free installation Quick and secure fixing 			
CB CLIP BLACK (5 MM)			
	20 Black CB Clips	CBC-5MM-BLK-20P	20
	100 Black CB Clips	CBC-5MM-BLK-100P	100
CB CLIP GREY (4 MM)			
	20 Grey CB Clips	CBC-4MM-GRY-20P	20
	100 Grey CB Clips	CBC-4MM-GRY-100P	100
CB CLIP NAVY (5 MM) FOR G-BRACKET-300 / G-BRACKET-400 ONLY			
	20 Navy CB Clips	CBC3-5MM-NAV-20P	20
	100 Navy CB Clips	CBC3-5MM-NAV-100P	100
CB CLIP BLUE (4 MM) FOR G-BRACKET-300 / G-BRACKET-400 ONLY			
	20 Blue CB Clips	CBC3-4MM-BLU-20P	20
	100 Blue CB Clips	CBC3-4MM-BLU-100P	100
CABLE TRAY CLIP (CT)			
 <ul style="list-style-type: none"> Prevents uplift and slide of cable tray Two sizes available to fit 2 mm and 3 mm thick steel Tool-free, quarter turn installation Quick and secure fixing 			
CT CLIP GREY (2 MM)			
	20 Grey CT Clips	CTC-2MM-GRY-20P	20
	100 Grey CT Clips	CTC-2MM-GRY-100P	100
CT CLIP BLACK (3 MM)			
	20 Black CT Clips	CTC-3MM-BLK-20P	20
	100 Black CT Clips	CTC-3MM-BLK-100P	100

Product information	Size	Product code	Order amount
KARABINER			
	<ul style="list-style-type: none"> Versatile fixing, easy to attach and detach Available in Stainless steel SWL up to 90 kg, 5:1 safety factor 		
	6x60 mm	KARA-6-60	10
	Stainless steel	KARA-6-60-S	10
	8x80 mm	KARA-8-80	10
	Stainless steel	KARA-8-80-S	10
G-BRACKET			
	<ul style="list-style-type: none"> Bespoke hanger for cable tray and basket, allowing easy loading and unloading of cables Available in 4 sizes to support cable tray or basket (100 mm, 200 mm, 300mm and 400mm) 		
	0 - 30 kg	G-BRACKET-100	1
	0 - 60 kg	G-BRACKET-200	1
	0 - 60 kg	G-BRACKET-300	1
	0 - 60 kg	G-BRACKET-400	1
G-BRACKET-SPACER			
	<ul style="list-style-type: none"> Joins two G-Brackets together, either vertically or horizontally allowing a central gap (min. 300 mm) Links different sizes of G-Bracket together SWL 30 kg, 5:1 safety factor 		
		G-SPACER	1
ADJUSTMENT KEY			
	<ul style="list-style-type: none"> Suitable for use on kit sizes No.1, No.2 and No.3 		
	No.1 - No.3	KEY-FLAG	1
ADJUSTMENT KEY			
	<ul style="list-style-type: none"> For use with Gripple kits Suitable for use on kit sizes No.4, No.5 and Catenary kits 		
	No.4 - No.5	KEY-P111147	1
WIRE CUTTERS (SMALL)			
	<ul style="list-style-type: none"> To trim excess wire rope Suitable for use on kit sizes No.1, No.2, No.3 and No.4 		
	No.1 - No.4	CUTTER-GRIPPLE	1
WIRE CUTTERS (LARGE)			
	<ul style="list-style-type: none"> To trim excess wire rope Suitable for use on kit sizes No.4, No.5 and 6mm Catenary kit 		
	No.4 - No.5	CUTTER-6MM	1
TORQ TENSIONING TOOL			
	<ul style="list-style-type: none"> Quickly and accurately tensions wire rope, suitable for use on kit sizes No.4, No.5 and 6 mm Catenary kit Delivers up to 100 kg of load with minimal effort 		
	No.6	CTI-D6MM-TOOL	1
PLASTIC SLEEVING			
	<ul style="list-style-type: none"> Creates a barrier against adverse reactions between dissimilar metals Available in two sizes, 2 mm and 3 mm, in lengths of 25 m 		
	2 mm	SLEEVE-2MM-25M	1
	3 mm	SLEEVE-3MM-25M	1

Product information	Size	Product code	Order amount
CEILING FIXING KIT			
	<ul style="list-style-type: none"> Improves aesthetics of No.1 hangers Suitable for use on suspended ceilings Conceals the Gripple hanger installation for improved aesthetics 		
	No.1	CEILING COVER	1
TWISTER			
	<ul style="list-style-type: none"> Tidies tail wires; improves aesthetics and safety of the final hanger installation For use with No.2 and No.3 Gripple hanger kits 		
	No.2 - No.3	TWIST-100BB	100
CORNER SADDLE			
	<ul style="list-style-type: none"> Plastic moulded product available with or without positioning magnets Prevents friction on rectangular ducting 		
	Standard	CORNER-SADDLE	10
	Magnetic	CORNER-SADDLE-MAG	10
WORK BELT			
	<ul style="list-style-type: none"> To store Gripple kits and accessories close to hand when installing Canvas material with adjustable waist belt 		
	One Size	WORKBELT	1
DECKING WEDGE			
	<ul style="list-style-type: none"> 18 mm version designed for use with Ribdeck S60 and Ribdeck 80 25 mm version designed for use with SMD R51, Comflor 51, Holorib, Multideck 50 and Metfloor 55 		
	18 MM	WEDGE8-18	1
	25 MM	WEDGE8-25	1
ALPHAWEDGE			
	<ul style="list-style-type: none"> Designed for use with Ribdeck E60 Adjustable and removable, no need for drilling specialist tools or skills 		
	No.2 - No.3	WEDGE-AMD-M8	1
MULTIWEDGE 2			
	<ul style="list-style-type: none"> Designed for use with Kingspan Multideck 60 and 80 Adjustable and removable, no need for drilling specialist tools or skills 		
	No.2 - No.3	MW2-MULTIWEDGE-M8	1
TR60 WEDGE			
	<ul style="list-style-type: none"> Designed for use with Structural Metal Decks TR60+ and TR80+ Adjustable and removable, no need for drilling specialist tools or skills 		
	M8	TR60-WEDGE-M8	1
	M10	TR60-WEDGE-M10	1
MF WEDGE			
	<ul style="list-style-type: none"> Ideal for fixing into Metfloor 60 and 80 profiles manufactured by Composite Metal Flooring The only fixing recommended by the decking manufacturer 		
	M8	WEDGE-MF	1
	M10	WEDGE-MF-M10	1
MINI HELIX SCREW			
	<ul style="list-style-type: none"> To be used with InvisiGrip (IG1), Express Hanger (XP1) and Standard Hanger (HF1) kits 		
		MINI-HELIX-SCREW-BULK	10
ACOUSTIC SPRING ANCHOR			
	<ul style="list-style-type: none"> To be used with InvisiGrip, Angel Hook, Express Hanger and Standard Hanger kits 		
	Standard	SPG-ANC-AC-38MM-45D	1
	Large	SPG-ANC-AC-75MM	1
Universal Bracket End Cap			
	<ul style="list-style-type: none"> To be used with Universal Brackets to provide a clean finish to the ends of brackets. 		
	41.5mm	UB-ENDCAP-100PK	1